



## 2m USB 2.0 Type A to C Cable, Anthra Line

No.: 36887

USB Type A Male to C Male

### Description

- Professional choice USB 2.0 Type A to C cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, gold plated connectors and contacts
- Double shielded cable, corrosion resistant tinned copper conductors
- 10 year warranty

The Anthra Line USB 2.0 Type A to C cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain signal integrity and reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 2.0 Type A to C cables are available in the following lengths: 0.5m, 1m, 2m and 3m

### Technical details

#### Connectors

- Connector A: USB 2.0 Type A Male
- Connector B: USB 2.0 Type C Male
- Housing Material: PVC
- Shielding in head shell: Copper foil
- Connector Plating: Gold
- Pin Construction:
  - A: Brass
  - C: Copper
- Pin Plating: Gold
- Dimensions [approx.] WxDxH:
  - A: 15.5x35.1x7.8mm [0.61x1.38x0.31in]

C: 11.0x25.5x7.3mm [0.43x1.00x0.29in]

**Cable Construction**

Length: 2m [6.56ft]

Standard: USB 2.0

Power Delivery: -

Colour: Black

Type: Round

Jacket Diameter: 3.5mm [0.14in]

Jacket Material: PVC

Conductor Material: Tinned Copper

Conductor Gauge Power: 28AWG

Conductor Gauge Data: 28AWG

Shielding: Aluminium Magnesium Braid 82%

**Specifications**

Supported Bandwidth: 480Mbps

Maximum Resolution: -

Nominal Attenuation: 0.5-400MHz < 5.8dB

Minimum Bend Radius: 25mm [0.98in]

Operating Temperature: 0°C - 40°C [32°F - 104°F]

Storage Temperature: 0°C - 70°C [32°F - 158°F]

**Miscellaneous**

Packaging Type: Polybag

Warranty (Years): 10

Product Compliance: RoHS, REACH, California Proposition 65 & UL

**Purchasing Information**

No. 36887

EAN: 4002888368872

**This product is also available in other lengths**

36885 - 0.5m [1.64ft]

36886 - 1m [3.28ft]

36887 - 2m [6.56ft]

36888 - 3m [9.84ft]